MANUFACTURERS ADDRESS : 1101 THIRD STREET SOUTH, MINNEAPOLIS, MN 55415 MFG TELEPHONE NUMBER : (612) 332-7371

24 HR EMERGENCY PHONE NO : 1-888-345-5732 CHEMICAL NAME OR FAMILY : PAINT PRODUCT FORMULA : NOT APPLICABLE

TRADE NAME : 80 6416 S/EFF VEN PLS PROT

ISSUE DATE : 03-13-02 DATE PRINTED : 09-03-02

\*\*\*\*\*\*\*\* INGREDIENTS \*\*\*\*\*\*

> WT % NAME

COMMON( 1):CRYSTALLINE SILICA .1-1.0% TLV TWA 0.10 MG/CU M

TLV STEL NOT ESTAB

CAS: 14808-60-7 CHEMICAL: QUARTZ OSHA PEL 0.10 MG/CU M

CEILING NOT ESTAB RECOMND NOT ESTAB

THERE ARE NO SARA 313 CHEMICALS IN THIS PRODUCT

(1) = THIS MATERIAL IS A CARCINOGEN PER NTP, IARC

ALL COMPONENTS OF THIS PRODUCT ARE IN COMPLIANCE WITH U.S. TSCA CHEMICAL SUBSTANCE INVENTORY REQUIREMENTS.

\*\*\*\*\*\*\* SECTION 3: PHYSICAL DATA \*\*\*\*\*\*

BOILING POINT: 212 DEG F. ( 100 DEG C.)

VAPOR PRESSURE MM HG AT 77 DEG F. ( 25 DEG C.): 24.0

VAPOR DENSITY (AIR = 1.0): 2.6

SPECIFIC GRAVITY: 1.14

PERCENT VOLATILE BY VOLUME: 74.61

EVAPORATION RATE (BUTYL ACETATE = 1): .4

SOLUBILITY IN WATER: YES

APPEARANCE/ODOR: NORMAL FOR A COATINGS PRODUCT.

PH : N.AV

COEFFICIENT OF WATER/OIL DISTRIBUTION: N.AV

\*\*\*\*\*\*\* SECTION 4: FIRE AND EXPLOSION HAZARD \*\*\*\*\*\*\*\*\*\*

FLASH POINT TCC/PM DEG F: 212 FLASH POINT TCC/PM DEG C: 100 LOWER EXPLOSIVE LIMIT : NA UPPER EXPLOSIVE LIMIT : NA

AUTO IGNITION - DEG F : N.AV DEG C : N.AV SENSITIVITY TO IMPACT : NONE

SENSITIVITY TO STATIC DISCHARGE: N.AV

EXTINGUISHING MEDIA: CARBON DIOXIDE, DRY CHEMICAL, FOAM, AND/OR WATER FOG.

SPECIAL FIRE FIGHTING PROCEDURES:

FIRE FIGHTERS MUST WEAR SELF CONTAINED BREATHING APPARATUS OR AIR MASKS. CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL WITH WATER SPRAY.

## VALSPAR CORPORATION MATERIAL SAFETY DATA SHEET

PAGE 2 80-0006416

\*\*\*\*\*\*\*\*\*\*\*\*\* SECTION 4: FIRE AND EXPLOSION HAZARD UNUSUAL FIRE AND EXPLOSIVE HAZARDS:

\*\*\*\*CONTINUED\*\*\*\*

NONE

\*\*\*\*\*\*\* HEALTH HAZARD DATA

\*\*\*\*\*\*\*\*\*

THRESHOLD LIMIT VALUE: NOT REQUIRED FOR MIXTURE.

EFFECTS OF OVEREXPOSURE:

IMMEDIATE EFFECTS (ACUTE):

OVEREXPOSURE TO INGREDIENTS IN THIS PRODUCT MAY CAUSE EYE IRRITATION, RESPIRATORY TRACT IRRITATION.

DELAYED EFFECTS (CHRONIC):

CONTAINS CRYSTALINE SILICA. THE IARC HAS DETERMINED THAT CRYSTALLINE SILICA INHALED IN THE FORM OF QUARTZ OR CRISTOBABLITE FROM OCCUPATIONAL SOURCES IS CARCINOGENIC TO HUMANS (GROUP 1). REFER TO IARC MONOGRAPH 68 IN CONJUNCTION WITH THE USE OF THESE MATERIALS. THE NTP HAS ALSO DETERMINED THAT CRYSTALINE SILICA IS A KNOWN HUMAN CARCINOGEN IN THE FORM OF FINE, BREATHABLE PARTICLES. RISK OF CANCER DEPENDS ON DURATION AND LEVEL OF EXPOSURE. IN COATINGS PRODUCTS, RISK IS DUE PRIMARILY TO INHALATION OF SANDING DUST OR RESPIRABLE PARTICLES IN SPRAY MIST.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE - ANY RESPIRATORY OR SKIN CONDITION.

EMERGENCY AND FIRST AID PROCEDURES:

NONE

POSSIBLE ROUTES OF ENTRY: INHALATION, INGESTION, SKIN ABSORPTION.

THIS PRODUCT IS STABLE CONDITIONS TO AVOID: NONE

INCOMPATIBILITY: AVOID WATER-REACTIVE MATERIALS.

HAZARDOUS DECOMPOSITION PRODUCTS:

AMMONIA COMPOUNDS SILICON DIOXIDE NITROGEN OXIDES

CARBON DIOXIDE/MONOXIDE

HAZARDOUS POLYMERIZATION: NONE

VENTILATE AREA. REMOVE SPILLS WITH INERT ABSORBENT.

WASTE DISPOSAL METHOD:

DISPOSE IN CHEMICAL DISPOSAL AREA OR IN A MANNER THAT COMPLIES WITH LOCAL, STATE, PROVINCIAL AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

\*\*\*\*\*\*\*\* SECTION 8: SPECIAL PROTECTION INFORMATION \*\*\*\*\*\*\*\*\*\*

RESPIRATORY PROTECTION:

UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ABOVE APPLICABLE LIMITS, NO RESPIRATOR IS REQUIRED. IF RESPIRATOR IS REQUIRED, THE APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) SHOULD BE WORN DURING APPLICATION. FOLLOW RESPIRATOR MANUFACTURERS DIRECTIONS FOR RESPIRATOR USE.

## VALSPAR CORPORATION MATERIAL SAFETY DATA SHEET

PAGE 3 80-0006416

\*\*\*\*\*\*

\*\*\*\*\*\*\*\* SECTION 8: SPECIAL PROTECTION INFORMATION \*\*\*\*CONTINUED\*\*\*\*
VENTILATION:

REQUIRED WHEN SPRAYING OR APPLYING IN CONFINED AREA.

PROTECTIVE GLOVES: USUAL HAND PROTECTION FOR PAINT APPLICATION. EYE PROTECTION: FOR SPRAY APPLICATION, USE CHEMICAL GOGGLES AS A MINIMUM. OTHERWISE, USE SAFETY GLASSES WITH SIDE SHIELDS AS A MINIMUM.

OTHER PROTECTIVE EQUIPMENT: USUAL CLOTHING FOR PAINTING OPERATIONS.

## PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT STORE ABOVE 120 DEG F (49 DEG C). KEEP FROM FREEZING. EMPTY CONTAINERS MAY CONTAIN PRODUCT RESIDUE. DO NOT CUT, PUNCTURE OR WELD CONTAINERS. ALL LABEL WARNINGS MUST BE OBSERVED UNTIL CONTAINER HAS BEEN CLEANED, RECONDITIONED OR PROPERLY DISPOSED OF.

## ABBREVIATIONS USED:

OSHA-OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION;
IARC-INTERNATIONAL AGENCY FOR RESEARCH ON CANCER; LEL-LOWER EXPLOSIVE LIMITS;
UEL-UPPER EXPLOSIVE LIMITS; MG CU M-MILLIGRAMS PER METERS CUBED; MM-MILLIMETERS;
MPPCF-MILLIONS OF PARTICLES PER CUBIC FOOT; MSHA-MINE SAFETY AND HEALTH
ADMINISTRATION; NIOSH-NATIONAL INSTITUTE OF OCCUPATIONAL SAFETY AND HEALTH;
WHMIS-WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION SYSTEM; H-HOURS; HR-HOURS;
NA-NOT APPLICABLE; NOT EST-NOT ESTABLISHED; NTP-NATIONAL TOXICOLOGY PROGRAM;
PB-LEAD; PEL-PERMISSIBLE EXPOSURE LEVEL; PPM-PARTS PER MILLION;
TCC/PM-TAG CLOSED CUP/PENSKY-MARTEN; RECM-RECOMMENDED; TLV-THRESHOLD LIMIT VALUES.
N.AV-NOT AVAILABLE; N.AP-NOT APPLICABLE; C-CELSIUS; F-FAHRENHEIT

PREPARED BY: REGULATORY AFFAIRS DEPT.

MFG TELEPHONE NUMBER : (612) 332-7371

\*\*\*\*\*\*\*\*\*\* DISCLAIMER SECTION

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE. THE VALSPAR CORPORATION MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE DATA. THE VALSPAR CORPORATION FURTHER ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS, OR THIRD PARTIES CAUSED BY THIS MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THIS MATERIAL.